

## ACRIMONT 03S

### Acrylic polymer emulsion

#### CHEMICAL CHARACTERISTICS

<b>Appearance:</b>	liquid
<b>Colour:</b>	white
<b>Smell:</b>	characteristic
<b>Dry residue:</b>	35.0 % +/- 1.0 %
<b>pH (sol al 10%):</b>	8.0 - 9.0
<b>Charge:</b>	anionic

#### PRODUCT CHARACTERISTICS

ACRIMONT 03S is a very soft and elastic emulsion of acrylic resins.

ACRIMONT 03S in combination with our PULMONT series polyurethanes and WAXMONT series waxes gives the mixtures excellent covering properties, improving wet rubbing, resistance to yellowing and cutting of prints at high temperatures.

ACRIMONT 03S is widely used for articles intended for furniture, car upholstery, splits and shoe leather.

#### APPLICATIONS

ACRIMONT 03S is applied either by spray diluted in water or with a roller spreader.

**Revision 01 of 22/01/2025**

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

#### CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

[Info@chimont.it](mailto:Info@chimont.it) [www.chimontgroup.it](http://www.chimontgroup.it) – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001