

## AUSIMONT STS

### Polysiloxane in aqueous emulsion

#### CHEMICAL CHARACTERISTICS

<b>Appearance:</b>	viscous liquid
<b>Colour:</b>	white
<b>Smell:</b>	Characteristic
<b>Dry residue:</b>	18.0 – 22.0 %
<b>pH (sol al 10%):</b>	5.0 – 7.0
<b>Charge:</b>	anionic

#### PRODUCT CHARACTERISTICS

AUSIMONT STS is a touch modifier that is used for resin finishes.

AUSIMONT STS gives a warm, pleasant and very slippery feel. This feature helps improve dry and wet abrasion resistance.

#### APPLICATIONS

AUSIMONT STS is applied by spray diluted in water.

**Revision 01 of 17/01/2025**

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

#### CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

[Info@chimont.it](mailto:Info@chimont.it) [www.chimontgroup.it](http://www.chimontgroup.it) – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001