

PULMONT 10R

Polyurethane Binder

CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	Colourless
Smell:	Characteristic
Dry residue:	20.0 % +/- 1.0 %
pH (sol al 10%):	7.5 – 9.0
Charge:	Anionic

PRODUCT CHARACTERISTICS

PULMONT 10R is a very fine polyurethane resin, it forms a glossy and elastic film with a slight friction.

PULMONT 10R is a binder particularly suitable for improving adhesion and being used in the rolling prefunds, obtaining an excellent equalization, strong adhesion and good masking of the grain leather defects.

PULMONT 10R can also be used in coating mixtures on full grain leathers in combination with acrylic resins of the ACRIMONT series to improve adhesion and resistance to wet and dry rubbing.

APPLICATIONS

PULMONT 10R can be applied both by spray diluted in water and roller.

Revision 01 of 10/01/2025

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

Info@chimont.it www.chimontgroup.it – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001