

PULMONT 13S

Polyurethane adhesion promoter for covering finishes

CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	Semi-transparent White
Smell:	Characteristic
Dry residue:	23.0 % +/- 1.0 %
pH (sol al 10%):	10.0 +/- 1.0
Charge:	Anionic

PRODUCT CHARACTERISTICS

PULMONT 13S is an excellent adhesion promoter.

PULMONT 13S forms a glossy film with excellent covering and unifying properties.

PULMONT 13S is used in fixations and resin bottoms.

APPLICATIONS

PULMONT 10R can be applied both by spray and roller.

PULMONT 13S forms a semi-gloss and very elastic film with multiple uses, for example; it can be used as a partial component in resin substrates to improve adhesion and also directly inside fixatives to improve their physical properties.

Revision 01 of 07/01/2025

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

Info@chimont.it www.chimontgroup.it – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001