

PULMONT 15L

Aliphatic polyurethane binder

CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	Colourless and Opalescent
Smell:	Characteristic
Dry residue:	21.0 % +/- 1.0 %
pH (sol al 10%):	7.0 - 9.0
Charge:	Anionic

PRODUCT CHARACTERISTICS

PULMONT 15L is a polyurethane that creates a very hard film, lacking elasticity, glossy, with excellent anchoring, resistant to dry and wet abrasion. These strengths can be increased by adding the catalyst FIX ISO.

PULMONT 15L is mainly used in final fixatives.

APPLICATIONS

PULMONT 15L is applied in combination with protein binders like CASEMONT series and polyurethanes like PULMONT series.

It is recommended to use PULMONT 15L on skins like Box type, impregnated, leathers lacking elasticity, this because creating a very hard and non-elastic film could lead to cracks and openings of the fixative.

Ex: formulation for semi-gloss fixative

PULMONT 15L	20 %
PULMONT 41 m	20 %
CASEIMONT CSC	10 %
WATER	50%
FIX ISO	2 %

PULMONT 15L is applied both sprays diluted in water and roller with undiluted product

Revision 01 of 18/12/2024

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

Info@chimont.it www.chimontgroup.it – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001