

PULMONT 26M

Polyurethane resin in aqueous dispersion

CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	Whitish colour
Smell:	Characteristic
Dry residue:	14.5 % +/- 1.0 %
pH (sol al 10%):	8.0 +/- 1.0
Charge:	Anionic

PRODUCT CHARACTERISTICS

PULMONT 26M is a resin suitable as a fixative for upper and lining and in all water finishes where good dry and wet rubbing properties are required.

PULMONT 26M does not require touch modifiers as it already has a soft, silky hand.

APPLICATIONS

PULMONT 26M can be used both spray and roller.

PULMONT 26M can be used in combination with glossy polyurethanes to achieve the desired matt grade.

PULMONT 26M can be cross-linked with our FIX ISO to greatly increase the resistance to friction.

Revision 01 of 07/01/2025

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

Info@chimont.it www.chimontgroup.it – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001