

## PULMONT 48L

Polyurethane in aqueous dispersion

### CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	Whitish colour
Smell:	Characteristic
Dry residue:	17.0 % +/- 1.0 %
pH (sol al 10%):	8.0 – 9.0
Charge:	Anionic

### PRODUCT CHARACTERISTICS

PULMONT 48L is a medium-hard, low-elastic polyurethane with a high gloss finish used mainly in the final glossy fixatives.

PULMONT 48L has excellent resistance to dry, wet and light rubbing.

### APPLICATIONS

PULMONT 48L can be applied by spray diluted in water or roller.

Revision 01 of 15/01/2025

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

#### CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

[Info@chimont.it](mailto:Info@chimont.it) [www.chimontgroup.it](http://www.chimontgroup.it) – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001