

WAXMONT FIL

Filling Agent and wax

CHEMICAL CHARACTERISTICS

Appearance:	Fluid
Colour:	White
Smell:	Characteristic
Dry residue:	21.0 % +/- 1.0 %
pH (sol al 10%):	9.0 +/- 1.0
Charge:	Anionic

PRODUCT CHARACTERISTICS

WAXMONT FIL is a mixture of opaque waxes and fillers. Its use is essential to eliminate the stickiness in the coverings mixtures.

APPLICATIONS

WAXMONT FIL is used in the bottoms of resin mixtures or coverings in quantities ranging from 50 to 100 gr per kilo.

Revision 01 of 21/01/2025

Chemical-physical properties of the product have been determined in accordance with internal procedures by methods of analysis due to national and / or internationally recognised standards. The information contained in this data sheet are based on our current knowledge. Given the multiplicity of Factors that can influence the processing and use of our products, the customer is obliged to carry out its part tests and controls. No responsibility can Be taken by us for an incorrect use of the product

CHIMONT INTERNATIONAL SPA

Tel. +39 0571 447011 – Via Barsanti 32 – 56020 Capanne – Montopoli Valdarno (Pisa) Italy

Info@chimont.it www.chimontgroup.it – P.I./C.F. 01410250508 – R.E.A. Pisa n.125831

Chimont International S.p.A. is a certified company Uni En Iso 9001-Uni En Iso 14001 and Uni En Iso 45001